

8500

# DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

Wall Mount Design: The simple beauty of an open space.

## KEY FEATURES

### SPACE-SAVING

Design Maximizes  
Versatility

### LIFTING POWER

Powers 650 lbs. Doors

## SMART

**MyQ TECHNOLOGY** ENABLES YOU TO SECURELY MONITOR AND CONTROL YOUR GARAGE DOOR OPENER AND HOUSELIGHTS WITH YOUR SMARTPHONE, TABLET OR COMPUTER. REQUIRES PURCHASE OF INTERNET GATEWAY (828LM)\*

**ALERTS** CAN BE RECEIVED AS EMAIL OR POP-UP (PUSH) NOTIFICATIONS ON YOUR MOBILE DEVICE SO THAT YOU ALWAYS KNOW THE STATUS OF YOUR GARAGE DOOR AND HOUSELIGHTS.

## RELIABLE

**ULTRA-QUIET** ELIMINATES SOUND AND VIBRATION THROUGH THE CEILING - PERFECT IF YOU HAVE A HOME WITH A ROOM ABOVE OR NEXT TO THE GARAGE.

**BATTERY BACKUP** POWERS UP EVEN WHEN THE POWER'S OUT. (REQUIRES PURCHASE OF 475LM BATTERY BACKUP).

**WALL MOUNT DESIGN** FREES THE GARAGE CEILING OF HANGING OPERATORS AND RAILS AND OPENS UP THE SPACE FOR ADDITIONAL STORAGE.

**REMOTE LIGHT** DELIVERS 200 WATTS OF LIGHT WITH ADJUSTABLE LIGHT TIME DELAY.

**LIFETIME MOTOR** AND 5-YEAR PARTS WARRANTY. 1-YEAR BACKUP BATTERY WARRANTY (SOLD SEPARATELY). DELAY.

## SECURE

**TIMER-TO-CLOSE** AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

**SECURITY+ 2.0®** SENDS A NEW CODE WITH EVERY REMOTE CLICK.

**MOTION DETECTOR** AUTOMATICALLY TURNS ON THE LIGHT.

**THE PROTECTOR SYSTEM®** AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

**POWER LOCK DEADBOLT (041A6102)** ENSURES THE DOOR CANNOT BE FORCED OPEN.

\*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee.

## INCLUDED ACCESSORIES:

### 3-BUTTON REMOTE CONTROL

Operates up to 3 openers or MyQ Light Accessories.



893MAX

### MYQ® CONTROL PANEL

Allows any garage door opener manufactured since 1998 to be controlled by your smartphone, tablet or computer (when paired with the Internet Gateway) – provides the upgrade needed to utilize Security+ 2.0 and MyQ Technology.



888LM

### REMOTE LIGHT

Light your space the way you want to by placing this anywhere in the garage. Uses (2) 100 watt bulbs (not included).



380LM

## POWERFUL ADD-ONS:

### INTERNET GATEWAY

Connects the opener to the Internet, enabling smartphone control.



828LM

### REMOTE LIGHT CONTROL

Enables home lighting control through the garage remote or a smartphone.



825LM

### GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

### BATTERY BACKUP

Powers up even when power is out so you can get in your garage.



475LM

PRODUCT GUIDE 8500

DC BATTERY BACKUP CAPABLE WALL  
MOUNT GARAGE DOOR OPENER

**LiftMaster®**

# MASTERFUL ENGINEERING.

## MOTOR

- Heavy-Duty 24V DC
- Automatic Thermal Protection
- Permanent Lubrication

## POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

## MECHANICS

- **Steel Chassis and Plastic Cover**
- **Internal Chain and Sprocket Drive Mechanism** (63:1 Gear Reduction)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup

# STANDARD SPECS.



16.25"

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

**MAX. DOOR WEIGHT**  
650 lbs.\*

## DIMENSIONS

**Max. Door Size:** 14 ft. High by 18 ft. Wide. Max 180 Sq Ft.  
**Headroom Clearance Required:** 3 in. from Center of Torsion Bar

**7.6"**  
Per second for door to move upward

**7.6"**  
Per second for door to move downward

# SECURITY

## SECURITY+ 2.0®

### RADIO CONTROLS

Operating Range: **~200'**

Operating Temperature: -40°F to 150°F

### 3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band\*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

\*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

### ENCRYPTED CONTROLS

#### MyQ® Control Panel® (888LM)

- MyQand Security+ 2.0 Radio
- Timer-to-Close
- Motion Detecting: Hands free opener lights on
- Light Control: Turns opener lights on/off
- Lock Mode: Locks out remote controls
- Program remote controls, keypads and MyQ Accessories
- \*Because the radios reside in the control panel, alternate wired control panels should not be used with this operator.

# SMART

## MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ accessories\*.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.\*\*
- \*MyQ radio disabled in battery backup mode or when using Alternate Power System (580LM)
- \*\*Requires Internet Gateway Accessory Model (828LM)

## HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*\*\*)

\*\*\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

# ELECTRICAL

## LIGHTING

### REMOTE LIGHT (380LM)



- Remote light control fixture can be located anywhere in garage
- Number of bulbs: 2
- Maximum Wattage: 100 x 2
- Adjustable Time, Solid-State Delay (1.5-4.5 minutes)

# SHIPPING.

**SHIPPING WEIGHT**  
(in lbs.)



## CARTONS (1)

**CARTON 1:** 24" x 10" x 12"

- Garage Door Opener Head (8500)
- MyQ Control Panel (888LM)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors
- Power Door Lock (041A6102)
- Cable Tension Monitor
- Remote Light (380LM)

## SAFETY AND SECURITY.

- The Protector System Safety Reversing Sensors
- Battery Backup Capable compatible model 475LM (optional accessory)
- Alert-2-Close/Unattended Close Operation††
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices



†† Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.

© 2018 LiftMaster All Rights Reserved  
300 Windsor Drive, Oak Brook, IL 60523  
LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance  
UL® and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.  
LMGDCA8500 4/18